

Technical Parameters

Art.nr.:	FD P2.6
Description	P2.6 Cabinet 500x1000, 192x384 pixels, 800CD/m2, 3840Hz
Physical Parameter	
Type	Indoor
Pixel Pitch	2,6 mm
Pixel Density	147456 dots/m2
LED Type	SMD2020
Module Size	250x250 mm
Module Resolution	96x96 pixel
Cabinet Size	500x1000x47mm (WXHxD)
Cabinet Weight	11,2 kg/pcs
Optoelectronic Parameter	
Brightness	≈800 cd/m2
Viewing Angle	140/140 H/V°
Minimum Viewing Distance	2,6 m
Gray Scale	14 bits
Power Consumption	450/150 Max./Avg. W/m ²
Work Voltage	AC100-240V
Refresh Rate	≥3840 Hz
Brightness Adjustment	0-100%
Color Temperature	5000-9300K Adjustable
Application Parameter	
Operation System	Windows 10/11
Control Distance	<100 m (Cable); ≥100 m (Optical fiber transmission)
Storage Temperature	-40~ +85 °C
Operating Temperature	-0~ +50 °C
Operating Humidity	10-90% RH
Life Span	100000 Hours
IP Rating	IP30/IP30 Front/Rear
Maintenance	Front
Installation	Fixed

