


## Technical Parameters

<b>Art.nr.:</b>	<b>GC P1.95</b>
Description	P1.95 GOB Cabinet 500x500, 256x256 pixels, 800CD/m2, 3840Hz

### Physical Parameter

Type	Indoor
Pixel Pitch	1,95 mm
Pixel Density	262144 dots/m2
LED Type	SMD1515
Module Size	250x250 mm
Module Resolution	128x128 pixel
Cabinet Size	500x500x85 mm (WXHxD)
Cabinet Weight	6.5 kg/pcs



### Optoelectronic Parameter

Brightness	≈800 cd/m2
Viewing Angle	160/160 H/V°
Minimum Viewing Distance	1,95 m
Gray Scale	14 bits
Power Consumption	450/150 Max./Avg. W/m <sup>2</sup>
Work Voltage	AC100-240V
Refresh Rate	≥3840 Hz
Brightness Adjustment	0-100%
Color Temperature	5000-9300K Adjustable

### Application Parameter

Operation System	Windows 10/11
Control Distance	<100 m (Cable); ≥100 m (Optical fiber transmission)
Storage Temperature	-40~ +85 °C
Operating Temperature	-20~ +60 °C
Operating Humidity	10-90% RH
Life Span	100000 Hours
IP Rating	IP30/IP30 Front/Rear
Maintenance	Front
Installation	Fixed