

## Technical Parameters

<b>Art.nr.:</b>	<b>LF P3.91</b>
Description	P3.91 Floor Cabinet 500x1000, 128x256 pixels, 2500CD/m2, 1920Hz
<b>Physical Parameter</b>	
Type	Indoor/Floor
Pixel Pitch	3,91 mm
Pixel Density	65536 dots/m2
LED Type	SMD1921
Module Size	250x250 mm
Module Resolution	64x64 pixel
Cabinet Size	500x1000x80mm (WXHxD)
Cabinet Weight	25 kg/pcs
<b>Optoelectronic Parameter</b>	
Brightness	≈2500 cd/m2
Viewing Angle	140/140 H/V°
Minimum Viewing Distance	2,97 m
Gray Scale	14 bits
Power Consumption	576/192 Max./Avg. W/m <sup>2</sup>
Work Voltage	AC100-240V
Refresh Rate	≥1920 Hz
Brightness Adjustment	0-100%
Color Temperature	5000-9300K Adjustable
<b>Application Parameter</b>	
Operation System	Windows 10/11
Control Distance	<100 m (Cable); ≥100 m (Optical fiber transmission)
Storage Temperature	-30~ +70 °C
Operating Temperature	-20~ +60 °C
Operating Humidity	10-90% RH
Life Span	100000 Hours
IP Rating	IP31 Front/Rear
Maintenance	Front
Installation	Fixed

