

## Technical Parameters

<b>Art.nr.:</b>	<b>NC P2.5</b>
Description	P2.5 Cabinet 640x480, 256x192 pixels, 600CD/m2, 3840Hz
<b>Physical Parameter</b>	
Type	Indoor
Pixel Pitch	2,5 mm
Pixel Density	160000 dots/m2
LED Type	SMD2121
Module Size	320x160 mm
Module Resolution	128x64 pixel
Cabinet Size	640x480x60 mm (WXHxD)
Cabinet Weight	7.5 kg/pcs
<b>Optoelectronic Parameter</b>	
Brightness	≈800 cd/m2
Viewing Angle	140/140 H/V°
Minimum Viewing Distance	2,5 m
Gray Scale	14 bits
Power Consumption	450/150 Max./Avg. W/m <sup>2</sup>
Work Voltage	AC100-240V
Refresh Rate	≥3840 Hz
Brightness Adjustment	0-100%
Color Temperature	5000-9300K Adjustable
<b>Application Parameter</b>	
Operation System	Windows 10/11
Control Distance	<100 m (Cable); ≥100 m (Optical fiber transmission)
Storage Temperature	-40~ +85 °C
Operating Temperature	-20~ +60 °C
Operating Humidity	10-90% RH
Life Span	100000 Hours
IP Rating	IP30/IP30 Front/Rear
Maintenance	Front
Installation	Fixed

