

## Technical Parameters

<b>Art.nr.:</b>	<b>CC P1.56</b>
Description	P1.56 Cabinet 600x337.5, 500-800CD/m2, 3840Hz
<b>Physical Parameter</b>	
Type	Indoor
Pixel Pitch	1.56 mm
Pixel Density	409.600 dots/m2
LED Type	Flip-chip COB
Module Size	150x168.75 mm
Module Resolution	384x216 pixel
Cabinet Size	600x337.5x30mm (WXHxD)
Cabinet Weight	5.1 kg/pcs
<b>Optoelectronic Parameter</b>	
Brightness	500~800 cd/m2
Viewing Angle	160/160 H/V°
Minimum Viewing Distance	1,56 m
Gray Scale	16 bits
Power Consumption	500W/m <sup>2</sup>
Work Voltage	AC100-240V
Refresh Rate	≥2880~3840 Hz
Brightness Adjustment	0-100%
Color Temperature	6500K Adjustable
<b>Application Parameter</b>	
Operation System	Windows 10/11
Control Distance	<100 m (Cable); 20 km (Optical fiber cable)
Storage Temperature	-20~ +50 °C
Operating Temperature	-20~ +50 °C
Operating Humidity	30-75% RH
Life Span	100.000 Hours
IP Rating	IP45
Maintenance	Front
Installation	Fixed



Cabinet Size

